


POWERFLUSH FX2 flushing chemical

POWERFUL CHEMISTRY rapidly dissolves and mobilises rust, sludge and corrosion deposits



- Designed for use with CLEARFLOW and other power flushing pumps.
- Super strength to clear heavily sludged systems fast.
- Loosens system and radiator blockages when other products fail.
- One visit no need to pre-treat system.



PowerFlush FX2 is designed for use with CLEARFLOW power flushing pumps, and is the flushing chemical to choose for the most rapid and effective results. It is a vigorous 'one shot' flushing and descaling liquid which starts to work immediately upon addition to the system.

PowerFlush FX2 enables heating engineers to thoroughly cleanse a heating system in just one visit, a significant benefit when so many households have both partners working full time.

When using PowerFlush FX2 there is no need for a prior visit to pre-treat the system with flushing chemicals several days before the power flush, saving on expense and inconvenience.

PowerFlush FX2 rapidly dissolves and mobilises the rust, sludge and corrosion deposits which accumulate in systems as a result of gradual decay, whether from corrosion as a result of bad design and air

ingress, or lack of an effective corrosion inhibitor.

Removal of these deposits can cure or prevent problems such as completely or partially cold radiators, frequent circulator pump failure and boiler noises caused by debris accumulating in the heat exchanger.

Usage rate:

2.5 litres of PowerFlush FX2 should be used to treat a typical heating system of 100 litres capacity (approx. 10/12 radiators). 5 litres should be used if the system has severe flow problems, or has microbore pipe work.

Application:

For use with steel, stainless steel, copper, brass, bronze, and all plastic barrier pipe work.

For systems with aluminium radiators or boiler heat exchangers use Kamco HYPERFLUSH.

Pack sizes

- 1. Cartons of 4x5 litres (BFX202)
- 2. Cartons of 4x5 litres + 8 tubes of Neutralising Crystals (BFX204)
- 3. Cartons of 4x2.5 litres + 4 tubes of Neutralising Crystals (BFX205)
- 4. 10 litre drum (BFX206)
- 5. Power Flush 8-pack (BFX210): 4x5 FX2, 8 tubes of Neutralising Crystals, 8 litres of SystemSafe-DM inhibitor, 1 roll of pH paper



The KAMCO range of water treatment chemicals for the care, maintenance and protection of heating and cooling systems

Kamco Support technical expertise; help-line and spares service.









TEL: 01727 875020 | WWW.KAMCO.CO.UK | INFO@KAMCO.CO.UK Kamco, Unit 9, Curo Park, Frogmore, St Albans, Herts, AL2 2DD, UK KAMCO and CLEARFLOW are registered trademarks of Kamco Limited.