



ScaleBuster MISB24-ET Water Conditioner

The ScaleBuster by Kamco is a patented, maintenance-free physical water conditioner designed to prevent and reduce scale build-up and corrosion in water systems without the use of chemicals, salt, or electricity.

The ScaleBuster doesn't remove minerals from water (like a water softener does), but instead alters the structure of the mineral ions (mostly calcium and magnesium) using a catalytic process as water flows through the unit.

This change reduces the minerals' ability to form hard scale on surfaces like pipework, boilers, bathroom fittings and much more.



Product Features

- Chemical-Free Operation: No need for salts or chemicals, making in environmentally friendly.
- Dry Contact Anode: Requires no external power supply.
- Maintenance-Free: No moving parts or power supply required, resulting in low operating costs.
- Long Lifespan : Designed to last over 20 years without a need for replacement parts.
- Wide Range of Sizes: Available in sizes from 1/2" to DN600 across Residential, Industrial and Commercial applications.
- Global Approvals: WRAS, NSF, TUV and PTFE certified b KTW.

Competitor Comparisons

- Aquabion H25
- Inta Active Flo AF028
- Stuart Turner Water Conditioner 46-75
- Hydro HY-MAG DN25











Product Specification

Connection: I" BSP Internal DN25

Connection Fittings Supplied : $2 \times 28 \text{mm} \times 1^{\text{"}} \text{MI}$

Total Length: 298mm Outer Diameter: 44mm

Weight: 2.3kg

Nominal Pressure: 16 bar Nominal Flow Rate: 3.53m³/h **Design Flow Rate:** 7.9m³/h (2.22l/s) **Maximum Flow Rate:** 12.0m³/h (3.48 l/s) **Maximum Operating Temperature : 60°C**

Warranty: 10 years - No quibble return after a 1 year

EAN: 506013459 6195

Product Number: MISB24-ET

Lead free brass according to DIN EN 12164, CW724R, CW510L or bronze in accordance with BS EN 1982: 2008 CC481K / BS1400 PBI

Internal Components

Anode: Zinc Z2 to BS EN 1179: 2003 & Zinc in accordance with ASTM B418 Type2 or Type I/MIL-A-1800 I K

Turbulence Body: Polytetrafluoroethylene in accordance with BS EN ISO 13000-1:2005

Retaining Clip: SST316L





